

CE, RoHS

- IP54 Front
- IP40 Rear
- 100 ÷ 240Vac (Driver Inc.)
- 30W
- COB LED
- II
- cable
- 195x195 mm
- White
- Aluminium+PC
- 10°C
+40°C
- Driver 111x42x27mm
- 50000 hr (L80B20)



UGR
≤ 19

Group "0"
Photobiological
safety

CRI
≥ 85

LED
120 lm/W

Questo dispositivo è
munito di lampade
a LED integrate

| | | |
|-----|---|-------------|
| A++ | } | L E D |
| A+ | | |
| A | | |

100°

Pegaso LED with reflector and anti-glare optics, high brightness and comfortable luminous flux. High colour rendering index (CRI). Its elegant and light weight, but at the same time strong structure, makes it suitable for many applications such as shops, malls, offices, clinics and homes.

| Code | Input Driver Inc. | Watt | Lumen Out | CRI | Light source | Beam Angle | Body | Diffuser | Insulation Class | Front IP Rate | Rear Ip rate | IK rate |
|------------|-------------------|------|-----------|-------|--------------|------------|-----------|----------|------------------|---------------|--------------|---------|
| DWL1530-NW | 100-240Vac | 30W | 2689 | Ra>80 | LED | 100° | Aluminium | PC | II | 54 | 20 | 08 |
| DWL1530-WW | 100-240Vac | 30W | 2635 | Ra>85 | LED | 100° | Aluminium | PC | II | 54 | 20 | 08 |

