



Waterproof fixture with integrated LEDs with optics 120°. Suitable for application for the most varied installations; home, industrial and commercial, underground car parks and public areas. The IP65 rating makes it suitable for indoor and outdoor installations. Extruded body in white polycarbonate fire retardant and self-extinguishing, high resistant against mechanical stress. The front frosted diffuser ensures a uniform light distribution avoiding glare effect. The smooth fixture body finish make it easy maintenance and cleaning, essential to optimise the lighting efficiency.

120°

Questo dispositivo è munito di lampade a LED integrate

A+ A' A } LED

CRI ≥ 80

Photobiological Safety GR "0"

- IP65
- 100 ÷ 240Vac
- 60W
- SMD LED
-

- Cable
- White
- PMMA/PC
- Ta -20°C +45°C
- 50000 hr (L80B20)

Code	Input Volt	Watt	PFC	Lumen	CRI	LED Chip	Beam angle	Body	Difuser	Insulation class	IP Rate	IK Rate	Dimensions (mm)
PSL1566-NW	100+240Vac	60W	90	110 lm/W	Ra>80	SMD 2835	120°	PC	PC Opal	I	65	08	1500 x 80 x 62

Arena Luci s.r.l. si riserva la facoltà di modificare le caratteristiche dei prodotti senza obbligo di preavviso
Arena Luci s.r.l. reserve the right to change products specifications at anytime without prior notice